

Protection Pads

Polypropylene Pads

Code	Description	Size	Weight
SSX10047	Superslim Polypropylene Pad 6mm Fixes to end of Superslim Soldier	220 x 171 x 6	0.22kg
PSX10034	Paraslim Soldier Bearing Pad Fixes to end of Steel Soldier. Part of 2700 Paraslim Soldier assembly (PSX10033). Does not need to be called off separately	145 x 170 x 6	0.15 kg
PSX10035	Paraslim Tilt Plate Bearing Pad Fixes to face of Paraslim Tilt Plate. Part of Paraslim Undercarriage assembly (PSX10032). Does not need to be called off separately	145 x 145 x 6	0.12 kg

A set of dense white plastic pads used primarily in Paraslim applications. Provide a rigid bearing and a degree of protection for the beam or girder finish.

Neoprene Pads

Code	Description	Size	Weight
SSX10043	Neoprene Pad - Superslim Fixes to end of Superslim Soldier	220 x 172 x 6	0.34kg

A hireable black stiff rubber pad in the same pattern as a Superslim End Plate for use as follows:

1.



2.



3.



Fixed to the end of a Superslim Soldier in dead shore applications to take up any variations and negate the requirement for a rocking head.

Placed between a Rapidshor Tilt Head and Superslim primary beam to prevent the components sliding past each other for soffit angles between 5 and 20 degrees. (30 degrees with attention given to surface preparation)

Placed in a bolted joint to provide the small degree of required rotational suspension in machine skate mounted travellers or other structures.

Fixing of Pads

All pads fixed to end plates using 4No. M10x35 CSK Set Pins, M10 Nuts and M10 Special Rocking Head Washers (Codes BNU11005, BNU11001, SSU10029).

